



UNIVERSAL CLEANING SOLUTIONS

1200 Series

Hot-Water Pressure Washers

Delivering high pressure and flow, these models provide tremendous cleaning power where electricity is not available.

4.5 to 5.6 GPM @ 3000 to 4000 PSI



■ Hotsy® triplex, belt-drive, positive-displacement pump carries seven-year crankcase and lifetime manifold warranties.

■ Your choice of **Vanguard** or **Honda V-Twin gasoline** or **Deutz-Ruggerini diesel engines** provide hours of tough cleaning power.

■ **Upright, oil-fired burner** with stainless-steel coil skin is highly efficient and maintains constant temperature using diesel fuel, kerosene or home-heating oil.

■ **Simple, easy-to-use control panel** includes adjustable temperature control and heavy-duty heater switch.

■ **Roll-cage chassis** (optional) is designed to protect the machine's vital components. Comes with heavy-duty **lifting eye** for use with a crane or chain hoist.

■ **Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning.

▶ **Hose reel** (optional) makes hose mobility and storage easy and convenient.



■ **Built-in wand holder** provides convenient storage.

Model 1270SS: 4.5 GPM @ 4000 PSI
(Shown with optional roll-cage and skid)

■ **Rust-proof, non-contaminating polyethylene fuel tanks** include fuel gauge in cap.

■ **Heavy-duty trigger gun and wand** with insulated cool grips.

■ **Float tank** maintains constant pressure and flow while preventing sediment from entering the machine's components.

▶ **Model 1260SSG and Model 1290SSG** (shown) come equipped with a 2000 watt generator to power the 120-volt AC burner as well as auxiliary power for low-wattage accessories.



1200 Series Specifications



Model 1260SS

- 4.5 GPM @ 3000 PSI
- 16 HP Vanguard V-Twin Gasoline Engine

(Shown with optional wheel kit)

The 1200 Series hot-water pressure washers are designed for hours of rigorous cleaning performance!

Ideal for truck or trailer mounting, the engine-driven 1200 Series Hotsys are totally self-contained, field-portable and ready for your toughest cleaning tasks. The only source required is water! These powerful units are perfect for construction, agriculture, trucking, exterior maintenance or any industry that requires top cleaning performance and durability from their pressure washer.

Discover Hotsy's no-cost benefits

Choose the 1200 Series pressure washers for their power and reliability. Then enjoy the benefits of doing business with the leader in industrial cleaning equipment. You'll find more than 120 models of pressure washers to choose from, free on-site demos, factory-trained service people, pre-delivery dealer prep, on-site machine checkout, operator training, local parts and accessory inventory, and a quality warranty program.

Accessories to match your application

With their easy adaptability, the 1200 Series models are prime candidates for Hotsy's full line of accessories. You can custom tailor the washer to your specific requirements, making your cleaning jobs faster, easier and more efficient. Choose from portable wheel kits, extra hose lengths, roll cage, skids, hose reels, wand extensions, quick couplers, downstream detergent injector, foam applicator, wet sandblaster, rotating brush and more.

Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer, as well as protect it. Exclusive advanced-formula HCC additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings. This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.

Call today for a FREE Demo!

Find out for yourself why the Hotsy 1200 Series is the ideal solution for your most difficult cleaning tasks. Call your Hotsy Distributor today for all the details and a FREE on-site demonstration.



- 1260SS:** 4.5 GPM @ 3000 PSI; 16-HP Vanguard V-Twin gasoline engine; oil-fired water heater w/ 12-volt burner; ship wt. 630 lbs.
- 1260SSG:** 4.5 GPM @ 3000 PSI; 16-HP Vanguard V-Twin gasoline engine; oil-fired water heater; 2000 watt generator w/ 120-volt AC burner; ship weight 655 lbs.
- 1267SS:** 4.5 GPM @ 3000 PSI; 15.2-HP Deutz-Ruggerini diesel engine; oil-fired water heater w/ 12-volt burner; ship wt. 710 lbs.
- 1270SS:** 4.5 GPM @ 4000 PSI; 20-HP Honda V-Twin gasoline engine; oil-fired water heater w/ 12-volt burner; ship wt. 750 lbs.
- 1275SS:** 4.5 GPM @ 4000 PSI; 21-HP Vanguard V-Twin gasoline engine; oil-fired water heater w/ 12-volt burner; ship wt. 750 lbs.
- 1280SS:** 5.0 GPM @ 3500 PSI; 20-HP Honda V-Twin gasoline engine; oil-fired water heater w/ 12-volt burner; ship wt. 750 lbs.
- 1285SS:** 5.0 GPM @ 3500 PSI; 21-HP Vanguard V-Twin gasoline engine; oil-fired water heater w/ 12-volt burner; ship wt. 750 lbs.
- 1290SS:** 5.6 GPM @ 3000 PSI; 20-HP Honda V-Twin gasoline engine; oil-fired water heater w/ 12-volt burner; ship wt. 750 lbs.
- 1290SSG:** 5.6 GPM @ 3000 PSI; 20-HP Honda V-Twin gasoline engine; oil-fired water heater; 2000 watt generator w/ 120-volt AC burner; ship weight 775 lbs.
- 1295SS:** 5.6 GPM @ 3000 PSI; 21-HP Vanguard V-Twin gasoline engine; oil-fired water heater w/ 12-volt burner; ship wt. 750 lbs.

SPECIFICATIONS

Water Pump Volume:	1260SS, 1260SSG, 1267SS, 1270SS, 1275SS: 4.5 GPM (17.03 lpm); 270 GPH (1022.1 lph) 1280SS, 1285SS: 5.0 GPM (18.92 lpm); 300 GPH (1135.2 lph) 1290SS, 1290SSG, 1295SS: 5.6 GPM (21.19 lpm); 336 GPH (1271.4 lph)
Water Pump Pressure:	1260SS, 1260SSG, 1267SS, 1290SS, 1290SSG, 1295SS: 3000 PSI (206.9 BAR) 1280SS, 1285SS: 3500 PSI (241.3 BAR) 1270SS, 1275SS: 4000 PSI (275.8 BAR)
Water Pump:	Hotsy® triplex, belt-drive, positive-displacement pump; ceramic plungers; brass manifold; oil-bath crankcase.
Pump Drive:	1260SS/1260SSG: 16-HP Vanguard V-Twin gasoline engine. Electric or manual start (less battery). 1267SS: 15.2-HP Deutz-Ruggerini twin-cylinder diesel engine. Electric start (less battery). 1270SS, 1280SS, 1290SS/1290SSG: 20-HP Honda V-Twin gasoline engine. Electric start (less battery). 1275SS, 1285SS, 1295SS: 21-HP Vanguard V-Twin gasoline engine. Electric or manual start (less battery).
Oil-Fired Water Heater:	414,000 BTU/hr 12-volt DC or 398,000 BTU/hr 120-volt AC (G Models only), UL-listed burner; pressure-atomizing type, with automatic electric ignition. Your choice of #1 or #2 diesel, kerosene or #1 home heating oil as your fuel. Fuel filter with water separator standard. Removable, rust-proof polyethylene fuel tank with sediment drain. Fuel gauge in cap. 11-gallon capacity.
Heating Coil:	Schedule 80, ASTM A53 close coiling pipe; hydrostatic pressure tested; vertically fired. Heating coil is sheathed in a full-length, sheet-metal wrap. Equipped with an independently welded heat-retention baffle plate.
Stack Size:	10" diameter.
Controls:	Adjustable temperature controller, safety pressure relief valve, pressure switch, engine ON/OFF switch, key switch starter, unloader valve, water heater ON/OFF lighted rocker switch, hour meter (G models only) and dual-detergent valve.
Wand Assembly:	Trigger gun control; heavy-duty wand with insulated grips.
Nozzles:	Three color-coded, quick-connect stainless steel; 0°, 15° and 40° spray patterns.
Hose:	3/8" ID, 50 ft., wire braid, 4500 PSI working-pressure rated; burst pressure is at least 4 times working pressure; oil and chemical resistant. Swivel fittings and hose guards on both ends. (Model 1260SS, 1260SSG and 1267SS equipped with 3000 PSI working-pressure rated hose.)
Portability:	Optional
Optional Accessories:	Note: Not all accessories are available for each model. Ask your sales representative for details. Tube steel roll cage, channel steel or angle iron skids, portable gear, extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, wet sandblaster, rotating brush, foam applicator and hour meter. P/N 280183-Portagear Kit P/N 280811-Bolt-On Skid Kit P/N 280812-Bolt-On Roll-Cage Kit
Construction:	Heavy-gauge steel; angle-iron frame.
Finish:	High-gloss powder coat.
Dimensions:	L-42 1/2" (107.95 cm); W-31" (78.7 cm); H-50" (127 cm).



21 Inverness Way East, Englewood, Colorado 80112-5796
Tel: (303) 792-5200 1-800-525-1976 Fax: (303) 792-0547
e-mail: info@hotsy.com or visit our website: www.hotsy.com

Built with PRIDE
in the USA

P/N 768399F Printed in USA Effective 11/02 Supercedes 768399E (8/02)
Specifications and product descriptions subject to change without notice.
© 2002 Hotsy