



1310 Dayton Street  
Salinas, CA 93901  
Ph: 831-753-6100  
Fx: 831-753-6111  
www.greenrubber.com  
sales@greenrubber.com

## PRODUCT DATA SHEET

Belt Number:		MPV2080SMBL	
Belt Description:		MONO-PURE 2PLY TPV FDA BLUE SMOOTH X NEG. PYRAMID	
Thickness (nominal):	2.70 mm		0.106 inch
Weight:	3.00 Kg/m²		0.615 lbs/ft²
Maximum Width:	3000.00 mm		118.00 inch
Minimum Pulley or Knife Edge Diamter (With the recommended joint):	50.00 mm		2.00 inch
With the recommended joint & reverse flex, Overlap joint of fasteners:	75.00 mm		3.00 inch
Load for 1% Extension:	8.00 daN/cm		46.00 lbs/inch
Standard Tension:	0.50 %		
Continuous Operating Temperature Range:	-10 °C		14 °F
Conveying Surface:	Material:	PVC	
	Feature:	Satin/Smooth	
	Color:	Blue	
Underside:	Material:	PVC	
	Feature:	Negative Pyramid	
	Color:	Blue	
	Co-Efficient of Friction (μ) on steel:	0.6 - 0.7	
Belt Construction Features:		2 ply monofilament - cover both sides	
Recommended Jointing System: Overlap		Alternative Splices: Single Finger Finger Over Lap Finger Over Finger Lacing	
Anti-Static:	No		